

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

marked T 21 S R 6 W S 24 B T..

Hemlock, 12 ins. dia., bears S.4°W., 25 lks. dist.,

marked T 21 S R 6 W S 23 B T..

Fir, 40 ins. dia., bears N.64°W., 11 lks. dist.,

marked T 21 S R 6 W S 14 B T.

East, on random line, between secs. 13 & 24.

V.20½°E.

40.00 Set temp. qr. sec. cor.

80.70 Intersect East boundary of Town., 56 lks. North of cor. to
secs. 13, 24, 18 & 19.

N.89°36'West, on true line, between secs. 13 & 24.

Descend slope 15°.

12.50 Cross branch, 4 lks. wide, flows South; ascend 27°.

20.00 Cross ridge, bears N. & S.; descend 19°.

36.00 Branch, 2 lks., flows S.; ascend 25°.

40.35 Set post, 4 ins. dia., 4 ft. long, with marked stone in
ground, for qr. sec. cor., marked ¼ S on N. face; from
which

Fir, 40 ins. dia., bears N.27°E., 28 lks. dist.,

marked ¼ S B T.

Dogwood, 4 ins. dia., bears S.23°E., 24 lks. dist.,

marked ¼ S B T.

47.50 Slope 35°.

52.00 Cross ridge; descend 18°.

57.00 Ascend 18°.

60.70 Descend 27°.

66.00 Ascend 37°.

75.00 Top; descend 8°.

80.70 The cor. to secs. 13, 14, 23 & 24.

Sept. 29th, 1884.

North between sections 13 & 14.

V.20½°E.

Descend 15°.