

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

- 10.00 Branch, 1 lk. wide, flows NW.; ascend 20°.
- 12.00 Descend 24°.
- 14.00 Branch, 1 lk., flows West; ascend 12°.
- 20.00 Slope 40°.
- 38.75 Cross ridge; descend 27°.
- 40.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Fir, 18 ins. dia., bears N.66°W., 38 lks. dist., marked $\frac{1}{4}$ S. B T.
- Fir, 60 ins. dia., bears S.28°E., 42 lks. dist., marked $\frac{1}{4}$ S B T.
- 64.00 Branch, 4 lks. wide, flows NE.; ascend 30°.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 11, 12, 13 & 14, marked T 21 S S 13 on NE., R 6 W S 13 on SE., S 14 on SW., S 11 on NW. face, with 4 notches on S. & 1 on E. edge; from which
- Fir, 18 ins. dia., bears N.31°E., 106 lks. dist., marked T 21 S R 6 W S 12 B T.
- Fir, 30 ins. dia., bears S.25°E., 92 lks. dist., marked T 21 S R 6 W S 13 B T.
- Fir, 24 ins. dia., bears S.33°W., 14 lks. dist., marked T 21 S R 6 W S 14 B T.
- Fir, 24 ins. dia., bears N.14°W., 101 lks. dist., marked T 21 S R 6 W S 11 B T.
-
- East, on random line, between secs. 12 & 13.
- V.21 $\frac{1}{2}$ °E.
- 40.00 Set temp. qr. sec. cor.
- 80.50 Intersect East bound. of Town., 70 lks. North of cor. to secs. 7, 18, 12 & 13.
- Thence I run
- N.89°30'West, on true line, between secs. 12 & 13.
- Descend slope 20°.