

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

which

Fir, 16 ins. dia., bears N.74°E., 17 lks. dist.,

marked T 21 S R 6 W S 1 B T.

Fir, 16 ins. dia., bears S.11°E., 28 lks. dist.,

marked T 21 S R 6 W S 12 B T.

Fir, 12 ins. dia., bears S.41°W., 38 lks. dist.,

marked T 21 S R 6 W S 11 B T.

Fir, 16 ins. dia., bears N.18°W., 27 lks. dist.,

marked T 21 S R 6 W S 2 B T.

East, on random line, between secs. 1 & 12.

V.21°E.

40.00 Set temp. gr. sec. cor.

80.10 Intersect East boundary of Town., 30 lks. North of cor.
to secs. 1, 12, 6 & 7.

Thence I run

N.89°47'W., between sections 1 & 12.

Descend 27°.

10.00 Creek, 20 lks. wide, flows NW.; ascend 21°.

40.05 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in the ground, for gr. sec. cor., marked $\frac{1}{4}$ S on
N. face; from which

Fir, 10 ins. dia., bears N.14°E., 23 lks. dist.,

marked $\frac{1}{4}$ S B T.

Fir, 8 ins. dia., bears S.45°W., 27 lks. dist.,

marked $\frac{1}{4}$ S B T.

41.00 Descend 15°.

80.10 The cor. to secs. 1, 2, 11 & 12.

Knowing by having previously run the North boundary that
the line has been chained long, and that I will fall to
the East of cor. to secs. 35 & 36, out of limits, I
run this line

North, on a true line, between secs. 1 & 2.

V.20°E.