

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

North between secs. 34 & 35, on blank line.

V. $20\frac{1}{2}^{\circ}$ E.Descend slope 8° .2.00 Ascend slope 12° .

40.00 Found qr. sec. cor.

80.06 To cor. to secs. 26, 27, 34 & 35. Renewed the cor. by setting post, 6 ins. dia., 4 ft. long with marked stone, 12 ins. in ground, marked T 21 S S 26 on NE., R 6 W S 35 on SE., S 34 on SW., & 27 on NW. face, with 2 notches on E. and 1 on S. edges; from which

Fir, 12 ins. dia., bears N. 53° E., 14 lks. dist.,
marked T 21 S R 6 W S 26 B T.

Fir, 16 ins. dia., bears S. 18° E., 19 lks. dist.,
marked T 21 S R 6 W S 35 B T.

Dogwood, 8 ins. dia., bears S. 48° W., 5 lks. dist.,
marked T 21 S R 6 W S 34 B T.

Fir, 18 ins. dia., bears N. 10° W., 15 lks. dist.,
marked T 21 S R 6 W S 27 B T.

Thence North between secs. 26 & 27.

V. 21° E.Descend slope 18° .16.50 Cross branch, 2 lks., flows East; ascend slope 20° .21.00 Descend 17° .

27.25 Branch, 6 lks., flows SE.; along bottom.

28.75 Branch, 6 lks., flows SW.

30.50 Branch, 6 lks., flows East.

31.00 Branch, 2 lks., flows West; ascend 20° .

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which

Fir, 60 ins. dia., bears N. 46° E., 9 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 9 ins. dia., bears N. 64° W., 19 lks. dist.,
marked $\frac{1}{4}$ S B T.