

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

- 41.51 Cross branch, 4 lks. wide, flows SE.; ascend 17°.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 22, 23, 26 & 27, marked T 21 S S 23 on NE., R 6 W S 26 on SE., S 27 on SW., S 22 on NW. face, with 2 notches on E. & S. edges; from which
- Maple, 8 ins. dia., bears N.20°E., 29 lks. dist., marked T 21 S R 6 W S 23 B T.
- Fir, 16 ins. dia., bears S.46°E., 15 lks. dist., marked T 21 S R 6 W S 26 B T.
- Cedar, 12 ins. dia., bears S.28°W., 16 lks. dist., marked T 21 S R 6 W S 27 B T.
- Fir, 12 ins. dia., bears N.70°W., 48 lks. dist., marked T 21 S R 6 W S 22 B T.
-
- East, on random line, between secs. 23 & 26.
V.20°E.
- 40.00 Set temp. qr. sec. cor.
- 79.75 Intersect N. & S. line, 65 lks. North of cor. to secs. 23, 24, 25 & 26.
Thence N.89°32'W., between secs. 23 & 26.
Ascend slope 10°.
- 3.00 Descend 25°.
- 5.75 Branch, 4 lks., flows SE.; ascend 40°.
- 20.50 28°
- 32.50 Top of ridge & trail, N. & S.; descend 46°.
- 38.50 20°
- 39.87 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- Fir, 20 ins. dia., bears N.3°E., 31 lks. dist., marked $\frac{1}{4}$ S B T.
- Fir, 36 ins. dia., bears S.10°W., 56 lks. dist., marked $\frac{1}{4}$ S B T.
- 46.00 Ascend 40°.