

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS	East, on random line, between secs. 14 & 23. V. $21\frac{1}{2}^{\circ}$ E.
40.00	Set temp. qr. sec. cor.
79.60	The cor. to secs. 13, 14, 23 & 24. Thence West, on true line, between secs. 14 & 23. Descend 8° .
12.00	Slope 22° .
39.80	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Hemlock, 16 ins. dia., bears N. 79° E., 22 lks. dist., marked $\frac{1}{4}$ S B T. Alder, 12 ins. dia., bears S. 35° E., 8 lks. dist., marked $\frac{1}{4}$ S B T.
45.00	Branch, 5 lks., flows SW.; ascend 24° .
60.00	Descend 30° .
71.25	Branch, 1 lk., flows S.; ascend 45° .
75.50	Descend 48° .
79.60	The cor. to secs. 14, 15, 22 & 23.
	North between secs. 14 & 15. V. $21\frac{1}{2}^{\circ}$ E. Ascend slope 20° .
20.00	Cross ridge, E. & W.; descend 17° .
25.50	Slope 25° .
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Hemlock, 20 ins. dia., bears S. 53° E., 18 lks. dist., marked $\frac{1}{4}$ S B T. Hemlock, 14 ins. dia., bears S. 57° W., 25 lks. dist., marked $\frac{1}{4}$ S B T.
41.50	Branch, 3 lks., flows West; ascend 24° .
60.50	Descend 37° .
78.50	Branch, 3 lks. wide, flows W.; ascend 12° .