

Subdivisions of T. 21 S., R. 6 W.

CHAINS
80.00

Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 10, 11, 14 & 15, marked T 21 S S 11 on NE., R 6 W S 14 on SE., S 15 on SW., S 10 on NW. face, with 4 notches on S. & 2 on E. edge; from which

Fir, 40 ins. dia., bears N.45°E., 59 lks. dist., marked T 21 S R 6 W S 11 B T.

Cedar, 12 ins. dia., bears S.29°E., 32 lks. dist., marked T 21 S R 6 W S 14 B T.

Fir, 40 ins. dia., bears S.84°W., 45 lks. dist., marked T 21 S R 6 W S 15 B T.

Cedar, 16 ins. dia., bears N.56°W., 9 lks. dist., marked T 21 S R 6 W S 10 B T.

Oct. 3rd, 1884.

East, on random line, between secs. 11 & 14.

V.20½°E.

40.00 Set temp. qr. sec. cor.

79.80 Intersect N. & S. line, 30 lks. North of cor. to secs. 11, 12, 13 & 14.

Thence N.89°47'West, on true line, between secs. 11 & 14. Ascend slope 30°.

23.50 Cross ridge, N. & S.; descend slope 35°.

39.90 Set post, 4 ins. dia., 4 ft. long, 12 ins. in ground, with marked stone, for qr. sec. cor., marked ¼ S on N. face; from which

Fir, 48 ins. dia., bears N.21°E., 43 lks. dist., marked ¼ S B T.

Fir, 10 ins. dia., bears S.31°W., 67 lks. dist., marked ¼ S B T.

40.30 Branch, 2 lks. wide, flows N.; ascend 7°.

42.00 Branch, 1 lk., flows NE.

58.50 Cross ridge; descend 37°.

67.00 15°

79.80 The corner to secs. 10, 11, 14 & 15.