

Subdivisions of T. 21 S., R. 6 W.

CHAINS

North between secs. 10 & 11.

V. 20° E.

Ascend slope 12°.

21.00 Cross ridge, E. & W.; descend slope 30°.

33.00 Branch, 1 lk. wide, flows NW.; ascend 15°.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from whichFir, 40 ins. dia., bears S. 75° E., 48 lks. dist.,
marked $\frac{1}{4}$ S B T.Fir, 4 ins. dia., bears N. 14° W., 25 lks. dist.,
marked $\frac{1}{4}$ S B T.

50.50 Descend 13°.

62.00 Branch, 4 lks. wide, flows NW.; along level.

62.75 Branch, 4 lks. wide, flows NE.

63.25 Branch, 4 lks. wide, flows NW.

68.50 Branch, 4 lks. wide, flows NE.; ascend 20°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 2, 3, 10 & 11, marked T 21 S S 2 on NE., R 6 W S 11 on SE., S 10 on SW., S 3 on NW. face, with 5 notches on S. & 2 on E. edge; from which

Cedar, 10 ins. dia., bears N. 20° W., 11 lks. dist.,
marked T 21 S R 6 W S 3 B T.Hemlock, 10 ins. dia., bears S. 65° E., 43 lks. dist.,
marked T 21 S R 6 W S 11 B T.Hemlock, 10 ins. dia., bears S. 50° W., 26 lks. dist.,
marked T 21 S R 6 W S 10 B T.Cedar, 10 ins. dia., bears N. 70° E., 48 lks. dist.,
marked T 21 S R 6 W S 2 B T.

East, on random line, between secs. 2 & 11.

V. 21 $\frac{1}{2}$ ° E.

40.00 Set temp. gr. sec. cor.

80.00 Intersect N. & S. line, 30. lks. South of cor. to secs.