

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS 64.00	Branch, 3 lks. wide, flows West.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 21, 22, 27 & 28, marked T 21 S S 22 on NE., R 6 W S 27 on SE., S 28 on SW., S 21 on NW., with 3 notches on E. and 2 on S. edge; from which Fir, 48 ins. dia., bears N.20°E., 20 lks. dist., marked T 21 S R 6 W S 22 B T. Fir, 8 ins. dia., bears S.49°E., 15 lks. dist., marked T 21 S R 6 W S 27 B T. Fir, 10 ins. dia., bears S.33°W., 52 lks. dist., marked T 21 S R 6 W S 28 B T. Fir, 12 ins. dia., bears N.42°W., 42 lks. dist., marked T 21 S R 6 W S 21 B T.
	East, on random line, between secs. 22 & 27. V.20½°E.
40.00	Set temp. gr. sec. cor.
80.20	The cor. to secs. 22, 23, 26 & 27. Thence West, on true line, between secs. 22 & 27. Along flat.
20.50	Ascend 29°.
28.00	Top of ridge, N. & S.; descend 34°.
40.10	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked ¼ S on N. face; from which Fir, 16 ins. dia., bears S.45°E., 23 lks. dist., marked ¼ S B T. Fir, 10 ins. dia., bears N.45°W., 19 lks. dist., marked ¼ S B T.
46.75	Ascend 42°.
56.00	Cross spur; descend 26°.
75.00	Top; descend 30°.
80.20	The cor. to secs. 21, 22, 27 & 28.