

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS	
	S.89°51'W., on true line, between secs. 15 & 22.
	Descend 48°.
7.00	Ascend 30°.
17.00	Descend 17°.
30.50	Branch, 8 lks. wide, flows N.; ascend 35°.
40.12	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
	Hemlock, 20 ins. dia., bears S.60°W., 36 lks. dist., marked $\frac{1}{4}$ S B T.
	Fir, 36 ins. dia., bears N.7°E., 20 lks. dist., marked $\frac{1}{4}$ S B T.
48.50	Cross trail on top of ridge; descend 45°.
54.00	Slope 15°.
80.25	The cor. to secs. 15, 16, 21 & 22.
North between sections 15 & 16.	
	V.20°E.
	Ascend 10°.
5.50	Trail on top of ridge, E. & W.; descend 35°.
29.50	Branch, 10 lks. wide, flows West; ascend 25°.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
	Fir, 48 ins. dia., bears S.47°E., 30 lks. dist., marked $\frac{1}{4}$ S B T.
	Fir, 40 ins. dia., bears N.45°W., 68 lks. dist., marked $\frac{1}{4}$ S B T.
64.00	Cross ridge, course E. & W.; descend 33°.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 9, 10, 15 & 16, marked T 21 S S 10 on NE., R 6 W S 15 on SE., S 16 on SW., S 9 on NW. face, with 3 notches on E. and 4 on S. edges; from which
	Maple, 16 ins. dia., bears N.77°E., 49 lks. dist.,