

## Subdivisions of T. 21 S., R. 6 W.

CHAINS

marked T 20 S S 34 on NE., R 6 W C C S 3 on SE., T 21 S C C S 4 on SW. face, with 3 notches on E. & W. edges; from which

Alder, 16 ins. dia., bears N.54°W., 29 lks. dist., marked T 20 S R 6 W S 34 B T.

Alder, 20 ins. dia., bears S.57°E., 18 lks. dist., marked T 21 S R 6 W C C S 3 B T.

Fir, 24 ins. dia., bears S.22°W., 83 lks. dist., marked T 21 S R 6 W C C S 4 B T.

Oct. 8th, 1884.

From the cor. to secs. 4, 5, 32 & 33, on south bound. of township, I run

North between secs. 32 & 33.

V.21°E.

- 5.50 Branch, 2 lks. wide, flows West; ascend 18°.
- 15.00 Cross spur; descend 27°.
- 32.00 Ascend 20°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{2}$  S on W. face; from which
- Fir, 18 ins. dia., bears N.47°W., 18 lks. dist., marked  $\frac{1}{2}$  S B T.
- Laurel, 14 ins. dia., bears N.35°E., 11 lks. dist., marked  $\frac{1}{2}$  S B T.
- 47.50 Cross ridge; descend 24°.
- 70.50 Ascend slope 42°.
- 79.00 Cross ridge; thence along flat.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 28, 29, 32 & 33, marked T 21 S S 28 on NE., R 6 W S 33 on SE., S 32 on SW., S 29 on NW. face, with 4 notches on E. and 1 on S. edge; from which
- Fir, 10 ins. dia., bears N.20°E., 49 lks. dist., marked T 21 S R 6 W S 28 B T.