

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

- 80.29 Intersect N. & S. line, 18 lks. South of cor. to secs.
15, 16, 21 & 23.
Thence I run
S.89°52'W., on true line, between secs. 16 & 21.
Ascend slope 12°.
- 8.00 Cross trail on top of ridge, runs N. & S.; descend 20°.
- 40.14 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which
Fir, 12 ins. dia., bears N.34°W., 37 lks. dist.,
marked $\frac{1}{4}$ S B T.
Cedar, 10 ins. dia., bears S.80°E., 75 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 43.00 Ascend 17°.
- 61.50 Cross trail on ridge, N. & S.; descend 30°.
- 80.29 The cor. to secs. 16, 17, 20 & 21.
Oct. 10th, 1884.

North between sections 16 & 17.

V.20°E.

- Descend 29°.
- .50 Branch, 2 lks. wide, flows West; ascend 30°.
- 8.00 Descend 35°.
- 15.00 Branch, 1 lk. wide, flows West; ascend 34°.
- 22.00 Along flat.
- 38.00 Cross trail, E. & W.; descend 20°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which
Fir, 48 ins. dia., bears S.88°W., 14 lks. dist.,
marked $\frac{1}{4}$ S B T.
Fir, 48 ins. dia., bears S.10°E., 79 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 61.00 Branch, 1 lk. wide, flows East; ascend 33°.
- 72.00 Descend 30°.