

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 6 W.

CHAINS  
 28.00 Cross branch, 8 lks. wide, flows NW.; ascend 15°.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{2}$  S on W. face; from which

Fir, 30 ins. dia., bears N.32°W., 35 lks. dist., marked  $\frac{1}{2}$  S B T.

Fir, 36 ins. dia., bears N.83°E., 41 lks. dist., marked  $\frac{1}{2}$  S B T.

65.00 Cross spur; descend 27°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 4, 5, 8 & 9, marked T 21 S S 4 on NE., R 6 W S 9 on SE., S 8 on SW., S 5 on NW. face, with 4 notches on E. & 5 on S. edges; from which

Fir, 8 ins. dia., bears N.64°E., 44 lks. dist., marked T 21 S R 6 W S 4 B T.

Fir, 10 ins. dia., bears S.74°E., 43 lks. dist., marked T 21 S R 6 W S 9 B T.

Fir, 48 ins. dia., bears N.20°W., 28 lks. dist., marked T 21 S R 6 W S 5 B T.

Fir,  $3\frac{1}{2}$  ins. dia., bears S.16°W., 97 lks. dist., marked T 21 S R 6 W S 8 B T.

Oct. 11th, 1884.

East, on random line, between secs. 4 & 9.

V.21 $\frac{1}{2}$ °E.

40.00 Set temp. gr. sec. cor.

80.37 Intersect N. & S. line, 35 lks. South of cor. to secs. 3, 4, 9 & 10.

Thence I run

S.89°45'W., on true line, between secs. 4 & 9.

Descend 9°.

29.00 Ascend 38°.

40.18 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{2}$  S on N. face; from which