

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

on SW. face, with 4 notches on E. and 2 on W. edges;
from which

Fir, 12 ins. dia., bears S.76°E., 79 lks. dist.,
marked T 21 S R 6 W S 4 C C B T.

Fir, 12 ins. dia., bears N.23°W., 58 lks. dist.,
marked T 20 S R 6 W S 33 B T.

Alder, 12 ins. dia., bears S.26°W., 69 lks. dist.,
marked T 21 S R 6 W S 5 B T.

From the cor. to secs. 31, 32, 5 & 6, on south boundary
of township,

North between secs. 31 & 32.

V.20°E.

Ascend slope 15°.

12.00 Cross ridge, E. & W.; descend 16°.

33.00 Along flat.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which

Hemlock, 14 ins. dia., bears S.25°W., 24 lks. dist.,
marked $\frac{1}{4}$ S B T.

Dogwood, 3 ins. dia., bears S.36°E., 29 lks. dist.,
marked $\frac{1}{4}$ S B T.

53.00 Ascend 11°.

70.00 Descend 15°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 29, 30, 31 & 32,
marked T 21 S S 29 on NE., R 6 W S 32 on SE., S 31 on
SW., S 30 on NW. face, with 5 notches on E. and 1 on
S. edge; from which

Fir, 3 ins. dia., bears N.23°E., 40 lks. dist.,
marked T 21 S R 6 W S 29 B T.

Fir, 40 ins. dia., bears S.86°E., 30 lks. dist.,
marked T 21 S R 6 W S 32 B T.

Cedar, 10 ins. dia., bears N.85°W., 42 lks. dist.,