

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

- 11.00 Stream, 30 lks. wide, flows SW.; ascend 28°.
- 15.00 Descend 33°.
- 21.00 Branch, 4 lks. wide, flows NW.; ascend 27°.
- 36.60 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{2}$ S on N. face; from which
- Fir, 8 ins. dia., bears N.7°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.
- Fir, 8 ins. dia., bears S.14°W., 21 lks. dist., marked $\frac{1}{4}$ S B T.
- 42.00 Along flat.
- 61.00 Ascend 27°.
- 70.75 Descend 36°.
- 76.60 The cor. to secs. 29, 30, 31 & 32.
- Oct. 13th, 1884.

North between secs. 29 & 30.

V.21°E.

- Descend 27°.
- 20.75 Gulch; ascend 16°.
- 33.00 Descend 27°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{2}$ S on W. face; from which
- Fir, 12 ins. dia., bears N.47°W., 8 lks. dist., marked $\frac{1}{4}$ S B T.
- Fir, 8 ins. dia., bears N.46°E., 17 lks. dist., marked $\frac{1}{4}$ S B T.
- 43.00 Cross stream, 15 lks. wide, flows West; ascend 18°.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 19, 20, 29 & 30, marked T 21 S S 20 on NE., R 6 W S 29 on SE., S 30 on SW., S 19 on NW. face, with 5 notches on E. and 2 on S. edges; from which
- Fir, 16 ins. dia., bears N.38°E., 32 lks. dist.,