

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

- 4.50 Descend 30°.
- 35.70 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- Maple, 4 ins. dia., bears S.10°W., 31 lks. dist., marked $\frac{1}{4}$ S B T.
- A fir, 30 ins. dia., bears N.88°W., 32 lks. dist., marked $\frac{1}{4}$ S B T.
- 47.70 Slope 30°.
- 72.70 Cross stream, 10 lks. wide, flows South; ascend 21°.
- 75.70 The cor. to secs. 19, 20, 29 & 30.

Oct. 14th, 1884.

North between sections 19 & 20.

V.20°E.

Descend 9°.

- 4.00 Branch, 6 lks. wide, flows SW.; ascend 18°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Fir, 10 ins. dia., bears S.52°W., 74 lks. dist., marked $\frac{1}{4}$ S B T.
- Dogwood, 6 ins. dia., bears S.78°E., 56 lks. dist., marked $\frac{1}{4}$ S B T.
- 74.00 Cross spur, E. & W.; descend 35°.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 17, 18, 19 & 20, marked T 21 S S 17 on NE., R 6 W S 20 on SE., S 19 on SW., S 18 on NW. face, with 4 notches on E. & 3 on S. edges; from which
- Fir, 14 ins. dia., bears N.25°W., 30 lks. dist., marked T 21 S R 6 W S 18 B T.
- Fir, 14 ins. dia., bears N.21°E., 37 lks. dist., marked T 21 S R 6 W S 17 B T.
- Maple, 12 ins. dia., bears S.45°E., 13 lks. dist.,