

Subdivisions of T. 21 S., R. 6 W.

CHAINS

ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

Fir, 40 ins. dia., bears N.3°W., 34 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 36 ins. dia., bears S.2°W., 41 lks. dist., marked $\frac{1}{4}$ S B T.

41.75 Descend 37°.

47.00 Ascend 43°.

56.00 Descend 39°.

74.75 The cor. to secs. 17, 18, 19 & 20.

Oct. 15th, 1884.

North between sections 17 & 18.

V.21°E.

Descend 27°.

21.00 Cross gulch; ascend 28°.

35.00 Cross spur; descend 37°.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which

Fir, 50 ins. dia., bears N.13°W., 133 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 24 ins. dia., bears N.18°E., 39 lks. dist., marked $\frac{1}{4}$ S B T.

49.00 Gulch; ascend 27°.

73.00 Cross ridge; descend 22°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 7, 8, 17 & 18, marked T 21 S S 8 on NE., R 6 W S 17 on SE., S 18 on SW., S 7 on NW. face, with 5 notches on E. & 4 on S. edges; from which

Fir, 30 ins. dia., bears N.46°E., 30 lks. dist., marked T 21 S R 6 W S 8 B T.

Fir, 5 ins. dia., bears S.86°W., 24 lks. dist., marked T 21 S R 6 W S 18 B T.