

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

Fir, 8 ins. dia., bears S.10°E., 32 lks. dist.,
marked T 21 S R 6 W S 17 B T.

Fir, 4 ins. dia., bears N.40°W., 42 lks. dist.,
marked T 21 S R 6 W S 7 B T.

East, on random line, between secs. 8 & 17.

V.20½°E.

40.00 Set temp. gr. sec. cor.

79.90 Intersect N. & S. line, 31 lks. North of cor. to secs. 8,
9, 16 & 17.

Thence I run

N.89°47'West, on true line, between secs. 8 & 17.

1.20 Branch, 1 lk. wide, flows North; ascend 15°.

14.75 Trail on spur; descend 27°.

31.25 Branch, 3 lks. wide, flows N.; ascend 20°.

39.95 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked ¼ S on N,
face; from which

Fir, 6 ins. dia., bears N.5°E., 13 lks. dist.,
marked ¼ S B T.

Fir, 6 ins. dia., bears S.55°E., 12 lks. dist.,
marked ¼ S B T.

Thence along N. slope of mountain.

79.90 The cor. to secs. 7, 8, 17 & 18.

West, on random line, between secs. 7 & 18.

V.20°E.

40.00 Set temp. gr. sec. cor.

73.60 Intersect West boundary of Town., 82 lks. North of cor.
to secs. 12, 13, 7 & 18.

Thence I run

N.89°25'East, on true line, between secs. 7 & 18.

Descend 22°.

.25 Cross stream, 8 lks. wide, flows N.; ascend 27°.

33.60 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12