

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

Dry fir, 24 ins. dia., bears N.15°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.

Dry fir, 40 ins. dia., bears S.12°W., 24 lks. dist., marked $\frac{1}{4}$ S B T.

41.00 Top of ridge, NE. & SW.; descend 25°.

Along North slope of mountain.

73.60 The cor. to secs. 7, 8, 17 & 18.

Oct. 16th, 1884.

North between secs. 7 & 8.

V.20 $\frac{3}{4}$ °E.

Descend mountain 19°.

8.50 Gulch; ascend 30°.

25.00 Cross ridge, NE. & SW.; along West slope.

40.00 Set a post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which

Dry fir, 40 ins. dia., bears S.80°E., 65 lks. dist., marked $\frac{1}{4}$ S B T.

Dry fir, 40 ins. dia., bears N.13°W., 127 lks. dist., marked $\frac{1}{4}$ S B T.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 5, 6, 7 & 8, marked T 21 S S 5 on NE., R 6 W S 8 on SE., S 7 on SW., S 6 on NW. face, with 5 notches on E. & S. edges; from which

Alder, 4 ins. dia., bears N.63°E., 26 lks. dist., marked T 21 S R 6 W S 5 B T.

Alder, 4 ins. dia., bears S.12°E., 16 lks. dist., marked T 21 S R 6 W S 8 B T.

Alder, 4 ins. dia., bears S.43°W., 27 lks. dist., marked T 21 S R 6 W S 7 B T.

Fir, 12 ins. dia., bears N.75°W., 42 lks. dist.,