

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 6 W.

CHAINS

Fir, 40 ins. dia., bears N.65°E., 69 lks. dist.,  
marked  $\frac{1}{2}$  S B T.

Fir, 50 ins. dia., bears S.52°E., 73 lks. dist.,  
marked  $\frac{1}{2}$  S B T.

64.00 Branch, 4 lks. wide, flows North; ascend.

72.60 The cor. to secs. 5, 6, 7 & 8.

North, on true line, between secs. 5 & 6.

V.20 $\frac{1}{2}$ °E.

Along West slope of mountain; descend 10°.

24.25 South Fork of Smith River, 30 lks. wide, flows West.

40.00 Fir, 4 ins. dia. for gr. sec. cor., marked  $\frac{1}{2}$  S on West  
face; from which

Fir, 4 ins. dia., bears N.65°E., 4 lks. dist.,  
marked  $\frac{1}{2}$  S B T.

Fir, 5 ins. dia., bears S.52°W., 9 lks. dist.,  
marked  $\frac{1}{2}$  S B T.

41.50 Branch, 2 lks. wide, flows West; ascend 15°.

71.00 On top of ridge, NW. & SE.; descend 21°.

92.75 Intersect North boundary of Township, 10.25 East of cor.  
to secs. 31 & 32; found post much decayed and could  
not make bearing trees agree with the field notes given.  
Re-established this cor. by setting a post, 6 ins. dia.,  
4 ft. long, 12 ins. in ground, marked T 20 S S 32 on  
NE., T 21 S R 6 W S 6 on SE., R 6 W S 31 on NW. face,  
with 5 notches on E. & 1 on W. edge; from which old  
trees:

Hemlock, 14 ins. dia., bears N.2°E., 65 lks. dist.,  
marked T 20 S R 6 W S 32 B T.

Fir, 14 ins. dia., bears S.65°E., 21 lks. dist.,  
marked T 21 S R 6 W S 5 B T.

Maple, 6 ins. dia., bears S.21°W., 25 lks. dist.,  
marked T 21 S R 6 W S 6 B T.

Dogwood, 6 ins. dia., bears N.53°W., 40 lks. dist.,  
marked T 20 S R 6 W S 31 B T.