

## Subdivisions of T. 21 S., R. 9 W.

CHAINS	Descend	
38.90	Pass over spur	
40.00	Set Maple post $4\frac{1}{2}$ ft. long 4 ins. sq. 24 ins. diam. in the ground on steep hill side sloping NE, for 1/4 Sec. Cor. Marked $\frac{1}{4}$ S. on the N. face, from which A Fir, 48 ins. diam. bears N.8*30'E., 41 lks. dist. Marked $\frac{1}{4}$ S. B T. A Fir, 40 ins. diam. bears S.49*30'E., 50 lks. dist. Marked $\frac{1}{4}$ S. B T.	
52.15	Creek 2 lks. wide Course South Ascend	-500
62.50	Enter flat	
76.50	Ascend	
81.95	Intersected East Bdy. of Tp.417 lks. South of Cor. to Secs. 18 and 19 T 21 S R 8 W, which is a post 30 ins. above ground 4 ins. sq. marked T 21 S S 18 on the NE, R 8 W S 19 on the SE, R 9 W S 24 on the SW, and S 13 on the NW faces with 3 notches on the N and S edges, from which A Hemlock, 12 ins. diam. bears N.80*E., 40 lks.dist. Marked T 21 S R 8 W S 18 B T A Hemlock, 16 ins. diam. bears S.72*W., 46 lks.dist. Marked T 21 S R 9 W S 24 B T. The other bearing trees had been destroyed, I marked a Fir 6 ins. diam. bears S.45*E., 38 lks. dist. marked T 21 S R 8 W S 19 B T. I set a Fir post $4\frac{1}{2}$ ft. long 4 ins. sq. 24 ins. in the ground on top ridge at point of intersection for C. C. to Secs. 13 and 24 Marked C C T 21 S on the W, R 9 W S 24 on the S, and S 13 on the N. faces with 3 grooves on the N and S sides, from which A Hemlock 24 ins. diam. bears S.35*E., 21 lks. dist. Marked C C T 21 S R 9 W S 13 and 24 B T A Hemlock, 12 ins. diam. bears S.36*W., 89 lks. dist. Marked T 21 S R 9 W S 24 B T	