

## Subdivisions of T. 21 S., R. 9 W.

CHAINS		
	Ascend,	
26.25	Creek, 1 lk. wide, Course W.	
32.00	Pass over spur Course W.	
40.00	Set Sand Stone 20 x 8 x 6 in. 15 ins. in the ground on steep hill side and raised mound of stone along side for $\frac{1}{2}$ Sec. Cor. marked $\frac{1}{2}$ S on the W. face, from which An alder, 8 ins. diam. bears N.42*E., 70 lks. dist. marked $\frac{1}{2}$ S B T. A d. fir, 20 ins. diam. bears N.59*W., 40 lks. dist. marked $\frac{1}{2}$ S B T.	
40.25	Top of spur sloping N.80*W.	+175
	Descend	
46.25	Canyon, Course N.75*W.	-100
48.50	Pass over spur.	
52.75	Creek, 3 lks. wide, Course N.60*W.	-25
	Ascend,	
66.00	Top of Spur Course N.65*W.	+250-
	Descend,	
75.00	Enter green timber.	
81.00	Creek 1 lk. wide Course N.5*E.	
91.25	Creek 1 lk. wide Course N.10*W.	-200
100.00	Pass over spur Course N.60*W.	
103.25	To a point 6.31 chs. S.89*48'E. of an alder, 12 ins. diam., marked S 5 on the North and S 8 on the South sides. Set alder post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground on steep hill side sloping NW. at the point of intersection for closing cor. to Secs. 7 and 8, marked C C T 21 S R 9 W on the S., S 8 on the E., and S 7 on the W. face with 5 notches on S. and E. edges, from which A fir, 44 ins. diam., bears N.69*E., 68 lks. dist. marked C C T 21 S R 9 W S 7 and S B T. A maple, 8 ins. diam. bears S.25*E., 68 lks. dist. marked T 21 S R 9 W S 8 B T.	