

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

is N.0°41'W., 20.71 chs.; to the old $\frac{1}{4}$ sec. cor. is N.0°27'W., 19.26 chs. and the N. portion is N.0°27'W., 65.37 chs.

I commence at the old cor. of Tps. 21 S., Rs. 9 and 10 W., which is a badly decayed post, marked and witnessed as described by the surveyor general, except the NW-bearing tree is dead and fallen.

Alongside the old cor. set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for cor. of Tps. 21 S., Rs. 9 and 10 W., on the N. bdy. of T. 22 S., R. 9 W., with brass cap marked

T21S	
R10W	R9W
S36	S31

1919

from which

A fir, 16 ins. diam., bears N.46°E., 27 lks. dist., marked T 21 S R 9 W S 31 B T (Old B.T.)

A fir, 10 ins. diam., bears N.19°W., 48 lks. dist., marked T 21 S R 10 W S 36 B T (New B.T.)

Thence

N.1°25'E., resurveying the E. bdy. of sec. 36.

Descend steep NW. slope, through heavy timber and scattering undergrowth, 150 ft. to

- 3.75 Dry bed of stream, course W.; ascend S. slope 250 ft. to
- 9.20 Top of spur, slopes SW.; ascend along W. slope 70 ft. to
- 11.45 Top of spur, slopes NW.; descend steep N. slope 270 ft. to
- 17.25 Deep ravine, course SW.; ascend steep S. slope 460 ft. to
- 29.00 Top of spur, slopes SW.; descend NW. slope 270 ft. to
- 37.72 Intersect the old $\frac{1}{4}$ sec. cor., which is a decomposed sandstone, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 31 only and alongside the old cor. set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked

S31
1919