

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 34 ins. diam., bears N.7*E., 81 lks. dist. marked <math>\frac{1}{4}</math> S 31 B T (New B.T.)</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S.76*E., 29 lks. dist., marked <math>\frac{1}{4}</math> S 31 B T (Old B.T.)</p> <p>From the <math>\frac{1}{4}</math> sec. cor.</p> <p>N.0*32'E., resurveying the E. bdy. of sec. 36.</p> <p>Descend NW. slope, 140 ft. to</p>
3.15	<p>Creek, 6 lks. wide, course SW.; ascend steep S. slope 510 ft. to</p>
23.05	<p>(A point 120.00 chs. southing from cor. of secs. 24 and 25)</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor. of sec.36 only, with brass cap marked</p> <div style="text-align: center; margin: 20px 0;"> <math>\frac{1}{4}</math>              S36              1919         </div> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 30 ins. diam., bears S.2*W., 129 lks. dist., marked <math>\frac{1}{4}</math> S 36 B T.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N.77*W., 77 lks. dist., marked <math>\frac{1}{4}</math> S 36 B T.</p> <p>Continue ascent of SE. slope 210 ft. to</p>
28.85	<p>Top of ridge, bears NE. and SW.; descend NW. slope 320 ft. to</p>
38.31	<p>Intersect the old cor. of secs. 25, 30, 31 and 36, which is a decayed stake, marked and witnessed as described by the surveyor general. I obliterate marks on the SW. and NW. bearing trees and change this cor. to refer to secs. 30 and 31 only. Alongside the old cor. set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 30 and 31, with brass cap marked</p> <div style="text-align: center; margin: 20px 0;">             T21S              S30              S31              R9W              1919         </div>