

## Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

ence to the old bearing trees, which are as described by the surveyor general. I obliterate marks on the old SW. bearing tree and at the exact cor. point set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 30 only, with brass cap marked

↑  
S30  
1919

from which

A fir, 34 ins. diam., bears N.75\*30'E., 33 lks. dist. marked  $\frac{1}{4}$  S 30 B T (Old B.T.)

A fir, 58 ins. diam., bears S.20\*E., 27 lks. dist., marked  $\frac{1}{4}$  S 30 B T (New B.T.)

From this corner

N.0\*48'E., resurveying the E. bdy. of Sec. 25.

Ascend S. slope 240 ft. to

7.30 Top of ridge, bears E. and W.; descend N. slope 315 ft. to  
17.40 Dry bed of creek, course SW.; ascend SE. slope 300 ft. to  
25.33 (A point 40.00 chs. southing from the cor. of secs. 24 and 25)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 25 only, with brass cap marked

↑  
S25  
1919

from which

A hemlock, 16 ins. diam., bears S.20\*W., 53 lks. dist., marked  $\frac{1}{4}$  S 25 B T.

A fir, 12 ins. diam., bears N.65\*W., 50 lks. dist. marked  $\frac{1}{4}$  S 25 B T.

Continue ascent of SE. slope 215 ft. to

31.30 Top of spur, slopes SW.; descend NW. slope 210 ft. to  
36.70 Ravine, course W.; ascend SW. slope 30 ft. to  
38.95 Intersect the old cor. of secs. 19, 24, 25 and 30, which