

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

is a sandstone, marked and witnessed as described by the surveyor general. I obliterate marks on SW. and NW. bearing trees and change this cor. to refer to secs. 19 and 30 only and alongside the old cor. set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19 and 30 only, with brass cap marked

T21S
S19

S30
R9W
1919

from which

A fir, 18 ins. diam., bears N.30*E., 60 lks. dist., marked T 21 S R 9 W S 19 B T. (Old B.T.)

An alder, 12 ins. diam., bears S.46*E., 15 lks. dist., marked T 21 S R 9 W S 30 B T (Old B.T.)

From this cor.

N.0*19'E., resurveying the E. bdy. of sec. 25.

Continue ascend of SW. slope 135 ft. to

5.95 Summit of ridge, trail along top, bears NW. and SE.; descend NE. slope 170 ft. to

12.55 Bottom of descent; thence ascend gradually along E. slope 20 ft. to

20.20 Descend along E. slope 50 ft. to

26.38 (A point E. of the cor. of secs. 22, 23, 26 and 27)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 24 and 25, with brass cap marked

T21S;
S24;

S25
R10W
1919

from which

A hemlock, 18 ins. diam., bears S.56*W., 63 lks. dist., marked T 21 S R 10 W S 25 B T.

A fir, 60 ins. diam., bears N.42*W., 30 lks. dist., marked T 21 S R 10 W S 24 B T.