

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

cap marked

$\frac{1}{4}$
 S24
 1919

from which

A hemlock, 10 ins. diam., bears S.34*W., 46 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.

A fir, 9 ins. diam., bears N.84*W., 41 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.

26.60 Top of spur, slopes NW.; descend N. slope 65 ft. to

28.15 Dry bed of stream, course SW.; ascend steep S. slope 175
ft. to

31.80 Top of spur, slopes SW.; descend along W. slope 75 ft. to

36.60 Dry bed of stream, course SW.; ascend S. slope 90 ft. to

38.43 Intersect the old cor. of secs. 13, 18, 19 and 24, which
is a sandstone, firmly set, marked and witnessed as de-
scribed by the surveyor general, except the NE. bearing
tree has fallen. I obliterate marks on SW. and NW.
bearing trees and change this cor. to refer to secs. 18
and 19 only, and alongside the old cor. set an iron post,
3 ft. long, 2 ins. diam., 24 ins. in the ground, for
cor. of secs. 18 and 19, with brass cap marked

T21S
 S18
 S19
 R9W
 1919

from which

A fir, 30 ins. diam., bears N.84*E., 68 lks. dist.,
marked T 21 S R 9 W S 18 B T. (New B.T.)

A fir, 36 ins. diam., bears S.62*E., 36 lks. dist.,
marked T 21 S R 9 W S 19 B T (Old B.T.)

From this cor.

N.1*03'E., resurveying the E. bdy. of sec. 24.

Continue ascent of S. slope 95 ft. to

1.90 Top of spur, slopes SW.; descend NW. slope 90 ft. to