

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

A fir, 30 ins. diam., bears N.42*E., 10 lks. dist.,
marked $\frac{1}{4}$ S 18 B T (Old B.T.)

A fir, 36 ins. diam., bears S.66*E., 50 lks. dist.,
marked $\frac{1}{4}$ S 18 B T (New B.T.)

From this cor.

N.0*46'E., resurveying the E. bdy. of sec. 13.

Descend steep N. slope 484 ft. to

28.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 13 only, with brass cap mark-
ed

$\frac{1}{4}$
 S13
 1919

from which

A vine maple, 6 ins. diam., bears S.47*W., 20 lks.
dist., marked $\frac{1}{4}$ S 13 B T.

A fir, 30 ins. diam., bears N.38*W., 83 lks. dist.
marked $\frac{1}{4}$ S 13 B T.

Continue descent of N. slope 26 ft. to

30.25 Small stream, 1 lk. wide, course NE.; ascend gradually
along E. slope 20 ft. to

32.75 Top of small spur, slopes NE.; descend N. slope 100 ft. to

38.10 Stream, 15 lks. wide, course SW.; ascend S. slope 15 ft. to

39.57 Intersect the point for old cor. of secs. 7, 12, 13 and
18, located by reference to the old bearing trees. I
obliterate marks on the old SW. and NW. bearing trees
and at the exact cor. point set an iron post, 3 ft.
long, 2 ins. diam., 24 ins. in the ground, for cor. of
secs. 7 and 18, with brass cap marked

T21S
 S7
 S18
 R9W
 1919

from which

A maple, 10 ins. diam., bears N.80*E., 28 lks. dist.,
marked T 21 S R 9 W S 7 B T (Old B.T.)