

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

A maple, 20 ins. diam., bears S.48\*E., 43 lks. dist.,  
marked T 21 S R 9 W S 18 B T (Old B.T.)

From this cor.

N.0\*05'E., resurveying the E. bdy. of sec. 13.

Ascend S. slope 160 ft. to

- 3.95 Top of spur, slopes SW.; descend NW. slope 145 ft. to
- 11.50 Dry bed of stream, course SW.; ascend SE. slope 600 ft. to
- 27.80 Top of spur, slopes SW.; descend NW. slope 50 ft. to
- 29.42 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 12 and 13, with brass cap  
marked

T21S;  
S12|  
S13|  
R10W|  
1919

from which

A fir, 14 ins. diam., bears S.61\*W., 31 lks. dist.  
marked T 21 S R 10 W S 13 B T.

A fir, 8 ins. diam., bears N.60\*W., 8 lks. dist.  
marked T 21 S R 10 W S 12 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold on sandstone  
base; 2nd rate.

Timber, fir, alder and hemlock.

Undergrowth, salmonberry, huckleberry, vinemaple and salal.

N.0\*05'E., resurveying the E. bdy. of sec. 12.

Descend NW. slope, through heavy timber and dense under-  
growth, 240 ft. to

- 6.30 Ravine, course SW.; ascend S. slope 115 ft. to
- 8.68 Intersect the old  $\frac{1}{4}$  sec. cor., which is a stone, firmly  
set, marked and witnessed as described by the surveyor  
general. The old SE. bearing tree is dead. I obliterate  
marks on the old SW. bearing tree and change this cor.  
to refer to sec. 7 only and alongside the old cor. set