

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 7 only, with brass cap marked

†  
S7  
1919

from which

A fir, 9 ins. diam., bears N.86\*E., 13 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

A fir, 12 ins. diam., bears S.75\*E., 21 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

From this cor.

N.1\*02'W., resurveying the E. bdy. of sec. 12.

Ascend along W. and SW. slope 170 ft. to

- 7.50 Top of spur, slopes W.; descend steep NW. slope 600 ft. to
- 21.85 Ravine, course NE.; ascend gradually along E. slope.
- 23.75 Top of low spur, slopes NE.; descend N. slope 85 ft. to
- 25.64 Wassen Creek, 15 lks. wide, course W.; ascend SE. slope 120 ft. to
- 31.32 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 12 only, with brass cap marked

†  
S12  
1919

from which

A hemlock, 36 ins. diam., bears S.78\*W., 33 lks. dist., marked  $\frac{1}{4}$  S 12 B T.

An alder, 12 ins. diam., bears N.62\*W., 36 lks. dist., marked  $\frac{1}{4}$  S 12 B T.

Continue ascent of SE. slope 190 ft. to

- 38.69 Intersect the point for old cor. of secs. 1, 6, 7 and 12, located by reference to the old NW. bearing tree. At the exact cor. point set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for angle point, with