

Resurvey East Boundary, T. 21 S., R. 10 W.

CHAINS

brass cap marked

> AP  
1919

from which

A fir, 12 ins. diam., bears N.20°E., 34 lks. dist.,  
marked A P B T (New B.T.)

A fir, 14 ins. diam., bears N.63°W., 24 lks. dist.,  
marked A P B T (Old B.T.)

From this point

N.0°41'W., resurveying the E. bdy. of sec. 12.

Ascend SE. slope 30 ft. to

0.90 Top of spur, slopes SW.; descend NW. slope 90 ft. to

14.05 Ravine, course SW.; ascend 65 ft. to

15.95 Top of spur, slopes SW.; descend 17 ft. to

19.50 Ravine, course NW.; ascend 20 ft. to

20.71 Intersect the point for old closing cor. of secs. 6 and  
7, located by reference to the old bearing trees, which  
are as described by the surveyor general. At the exact  
cor. point set an iron post, 3 ft. long, 2 ins. diam.,  
24 ins. in the ground, for closing cor. of secs. 6 and  
7, with brass cap marked

T21S  
S6 — CC  
S7  
R9W  
1919

From this cor.

N.0°27'W., resurveying the E. bdy. of sec. 12.

Ascend SE. slope 270 ft. to

11.20 Top of ridge, bears NE. and SW.; descend NW. slope 30 ft.  
to

11.93 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of secs. 1 and 12, with brass cap marked

T21S  
S1  
S12  
R10W  
1919