

Resurvey East Boundary, T. 21 S., R. 10 W. 13735

CHAINS

from which

A fir, 22 ins. diam., bears S.33*W., 65 lks. dist.,
marked T 21 S R 10 W S 12 B T.

A fir, 36 ins. diam., bears N.10*W., 43 lks. dist.,
marked T 21 S R 10 W S 1 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold on sandstone
base, 2nd rate.

Timber, fir, cedar, hemlock and maple.

Undergrowth, salmonberry, vinemaple and salal.

N.0*27*W., resurveying the E. bdy. of sec. 1.

Descend NW. slope, through heavy timber and scattering
undergrowth, 250 ft. to

7.33 Intersect the point for the old $\frac{1}{4}$ sec. cor., located by
reference to the old bearing trees, which are marked as
described by the surveyor general. I now destroy all
evidence of this cor. and continue my line.

Descend N. slope 400 ft. to

17.00 Dry bed of creek in canyon, course NW.; ascend SW. slope
250 ft. to

28.45 Top of spur, slopes W.; descend NW. slope 180 ft. to

33.70 Ravine, course NW.; ascend SW. slope 210 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap
marked

$\frac{1}{4}$
S1:
1919

from which

A fir, 14 ins. diam., bears S.67*W., 35 lks. dist.
marked $\frac{1}{4}$ S 1 B T.

A fir, 11 ins. diam., bears N.10*W., 22 lks. dist.
marked $\frac{1}{4}$ S 1 B T.