

County Surveyor's Record, Douglas County, Oregon

SUBDIVISIONS OF T. 21 S., R. 10 W.,
 As surveyed by William Thiel, Deputy Surveyor,
 under Contract No. 342, dated October 6th, 1879.

CHAINS		
	I commence at the corner to Secs. 8, 9, 16 and 17, being a pyramidal stone 2 ft. by 2 ft., from which A Maple, 5 ins. diam., bears N.20*E., 14 lks. dist., in accordance with the field notes furnished by your office, thence	
	I run South, on line between Secs. 16 and 17. Va.20*E.	
	Descending.	
2.50	Gulch, course SE - commence ascent.	-80
5.50	Rocky bluff, commence descent.	+100
11.34	Fir, 60 ins. diam.	
16.75	Canyon, course E. commence ascending point.	
19.36	Cedar, 48 ins. diam., commence descending.	-150
21.50	Creek 75 lks. wide, course NE, commence ascending.	-50
25.77	Cedar, 50 ins. diam.	
32.25	Fir, 16 ins. diam.	
37.10	Cedar, 16 ins. diam.	
38.25	Top of spur, course E and W; begin descent.	
40.00	Set for $\frac{1}{4}$ Sec. corner a rock 32x10x10, from which A Fir, 36 ins. diam., bears S.51*W., 19 lks. dist. A Cedar, 6 ins. diam., bears N.86*E., 10 lks. dist.	+300
	Descend spur thick with Huckleberries.	
43.25	Gulch, a branch 2 lks. wide, course W.	-50
47.45	Begin ascent. Fir, 60 ins. diam.	
52.25	Top of ridge, course E and W. Begin descent.	+250
57.00	Fir, 60 ins. diam.	
60.25	Gulch, course W. Begin ascent.	-100
61.50	Top of spur, begin descent.	+50
65.25	Branch 2 lks. wide, course W., begin ascent.	-80
68.35	Fir, 60 ins. diam.	
80.00	Set a rock, (pointed) 24 ins. x 18x6 at foot of cliff 5 feet high, for corner to Secs. 16, 17, 20 and 21, from which	+300