

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

3.75 Dry bed of stream, course W., ascend S. slope 250 ft. to
 9.20 Top of spur, slopes SW; ascend along W. slope 70 ft. to
 11.45 Top of spur, slopes NW; descend steep N. slope 270 ft. to
 17.25 Deep ravine, course SW; ascend steep S. slope 460 ft. to
 29.00 Top of spur, slopes SW; descend NW slope 270 ft. to
 37.72 Intersect the old $\frac{1}{4}$ sec. cor. which is a decomposed sand-
 stone, marked and witnessed as described by the Surveyor
 General. I change this cor. to refer to sec. 31 only
 and alongside the old cor. set an iron post, 3 ft. long,
 1 ins. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of
 sec. 31 only, with brass cap marked

$\frac{1}{4}$
 | S31
 1919

from which

A Cedar, 34 ins. diam., bears N.7*E., 81 lks. dist.
 marked $\frac{1}{4}$ S 31 B T (New B.T.)

A Fir, 30 ins. diam., bears S.76*E., 29 lks. dist.
 marked $\frac{1}{4}$ S 31 B T (Old B.T.)

From the $\frac{1}{4}$ Sec. corner.

N.0*32'E., resurveying the E. bdy. of Sec. 36.

Descend NW slope, 140 ft. to

3.15 Creek, 6 lks. wide, course SW., ascend steep S. slope
 510 ft. to

23.05 (A point 120.00 chs. southing from cor. of Secs. 24 and
 25.)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 36 only, with
 brass cap marked

$\frac{1}{4}$
 S36 |
 1919

from which

A Hemlock, 30 ins. diam., bears S.2*W., 129 lks. dist.
 marked $\frac{1}{4}$ S 36 B T.

A Fir, 36 ins. diam., bears N.77*W., 77 lks. dist.
 marked $\frac{1}{4}$ S 36 B T.