

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

Continue ascent of SE slope 210 ft. to

28.85 Top of ridge, bears NE and SW; descend NW slope 320 ft. to

38.31 Intersect the old cor. of Secs. 25, 30, 31 and 36, which is a decayed stake, marked and witnessed as described by the Surveyor General. I obliterate marks on the SW and NW bearing trees and change this cor. to refer to secs. 30 and 31 only. Alongside the old cor. set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 30 and 31, with brass cap marked

T21S  
S30  
S31  
R9W  
1919

from which

A Cedar, 16 ins. diam., bears N.30\*E., 75 lks. dist. marked T 21 S R 9 W S 30 B T (Old B.T.)

A Cedar, 24 ins. diam., bears S.20\*E., 66 lks. dist. marked T 21 S R 9 W S 31 B T (old B.T.)

From this corner

N.1\*55'W., resurveying the E. bdy. of Sec. 36.

Descend steep NW slope 380 ft. to

13.45 Ravine, course NW; ascend steep SW slope 100 ft. to

21.80 Top of spur, slopes NW; descend N. slope 90 ft. to

24.75 (A point 80.00 chs. southing from cor. of Secs. 24 and 25)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 25 and 36, with brass cap marked

T21S  
S25  
S36  
R10W  
1919

from which

A Fir, 9 ins. diam., bears S.56\*W., 35 lks. dist., marked T 21 S R 10 W S 36 B T.

A Fir, 32 ins. diam., bears N.65\*W., 88 lks. dist., marked T 21 S R 10 W S25 B T.