

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

Land, mountainous.  
 Soil, sandy loam, sandstone bedrock, mostly shallow;  
 2nd rate.  
 Timber, Fir, Hemlock and Cedar.  
 Undergrowth, Salmonberry, Vinemaple and Salal.

N.1\*55'W., resurveying the East boundary of Sec. 25.  
 Descend steep NE slope, through heavy timber and  
 scattering undergrowth, 180 ft. to

5.80 Deep ravine, course NW., ascend SW slope 275 ft. to  
 14.68 Intersect the point for old  $\frac{1}{4}$  Sec. cor., located by  
 reference to the old bearing trees, which are as  
 described by the Surveyor General. I obliterate  
 marks on the old SW bearing tree and at the exact  
 corner point set an iron post, 3 ft. long, 1 in.  
 diam., 26 ins. in the ground, for  $\frac{1}{4}$  Sec. corner of  
 Sec. 30 only, with brass cap marked

$\frac{1}{4}$   
 | S30  
 1919

from which

- A Fir, 34 ins. diam., bears N.75\*30'E., 33 lks.  
 dist., marked  $\frac{1}{4}$  S 30 B T (Old B.T.)
- A Fir, 58 ins. diam., bears S.20\*E., 27 lks.  
 dist. marked  $\frac{1}{4}$  S 30 B T (New B.T.)

From this corner.

N.0\*48'E., resurveying the E. bdy. of Sec. 25.

Ascend S. slope 240 ft. to

7.30 Top of ridge, bears E and W; descend N. slope 315 ft. to  
 17.40 Dry bed of creek, course SW; ascend SE slope 300 ft. to  
 25.33 (A point 40.00 chs. southing from the cor. of Secs. 24  
 and 25)

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in