

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 25 only, with  
brass cap marked

$\frac{1}{4}$   
 S25  
 1919

from which

A Hemlock, 16 ins. diam., bears S.20\*W., 53 lks.  
dist., marked  $\frac{1}{4}$  S 25 B T.

A Fir, 12 ins. diam., bears N.65\*W., 50 lks.  
dist., marked  $\frac{1}{4}$  S 25 B T.

Continue ascent of SE slope 215 ft. to

31.30 Top of spur, slopes SW; descend NW slope 210 ft. to

36.70 Ravine, course W; ascend SW slope 30 ft. to

38.95 Intersect the old cor. of Secs. 19, 24, 25 and 30, which  
is a sandstone, marked and witnessed as described by  
the Surveyor General. I obliterate marks on SW and  
NW bearing trees and change this cor. to refer to Secs.  
19 and 30 only and alongside the old cor. set an iron  
post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,  
for cor. of Secs. 19 and 30 only, with brass cap  
marked

T21S  
 S19  
 S30  
 R9W  
 1919

from which

A Fir, 18 ins. diam., bears N.30\*E., 60 lks. dist.  
marked T 21 S R 9 W S 19 B T (Old B.T.)

An Alder, 12 ins. diam., bears S.46\*E., 15 lks. dist.  
marked T 21 S R 9 W S 30 B T (Old B.T.)

From this corner.

N.0\*19'E., resurveying the E. bdy. of Sec. 25.

Continue ascent of SW slope 135 ft. to

5.95 Summit of ridge, trail along top, bears NW and SE;  
descend NE slope 170 ft. to

12.55 Bottom of descent; thence ascend gradually along E.  
slope 20 feet to