

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

A Fir, 36 ins. diam., bears S.36*E., 38 lks. .
dist., marked $\frac{1}{4}$ S. 19 B T (New. B.T.)

From this cor.

N.0*09'E., resurveying the E. bdy. of Sec. 24.

Ascend SE slope 80 ft. to ridge.

7.20 Trail, bears NE and SW.

7.70 Summit of ridge, bears NE and SW; descend N. slope
560 ft. to

24.10 Stream, 2 lks. wide, course NW; ascend SW slope 60 ft.
to

26.49 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 24 only, with
brass cap marked

$\frac{1}{4}$
S24 |
1919

from which

A Hemlock, 10 ins. diam., bears S.34*W., 46 lks.
dist., marked $\frac{1}{4}$ S 24 B T.

A Fir, 9 ins. diam., bears N.84*W., 41 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.

26.60 Top of spur, slopes NW; descend N slope 65 ft. to

28.15 Dry bed of stream, course SW; ascend steep S. slope
175 ft. to

31.80 Top of spur, slopes SW; descend along W slope 75 ft. to

36.60 Dry bed of stream, course SW; ascend S slope 90 ft. to

38.43 Intersect the old cor. of Secs. 13, 18, 19 and 24, which
is a sandstone, firmly set, marked and witnessed as
described by the Surveyor General, except the NE
bearing tree has fallen. I obliterate marks on SW and
NW bearing trees and change this cor. to refer to
Secs. 18 and 19 only, and alongside the old cor. set
an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for corner of Secs. 18 and 19, with brass
cap marked

T21S
S18
S19
R9W
1919