

## RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

Surveyor General. I obliterate marks on the old bearing tree referring to Sec. 13 and change this cor. to refer to Sec. 18 only and alongside, the old corner set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 18 only, with brass cap marked

$\frac{1}{4}$   
 $\uparrow$   
 S18  
 1919

from which

A Fir, 30 ins. diam., bears N.42\*E., 10 lks.

dist., marked  $\frac{1}{4}$  S 18 B T (Old B.T.)

A Fir, 36 ins. diam., bears S.66\*E., 50 lks.

dist., marked  $\frac{1}{4}$  S 18 B T (New B.T.)

From this cor.

N.0\*46'E., resurveying the E. bdy. of Sec. 13.

Descend steep N. slope 484 ft. to

28.99 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of Sec. 13 only, with brass cap marked

$\frac{1}{4}$   
 $\uparrow$   
 S13  
 1919

from which

A Vinemaple, 6 ins. diam., bears S.47\*W., 20 lks.

dist., marked  $\frac{1}{4}$  S 13 B.T.

A Fir, 30 ins. diam., bears N.38\*W., 83 lks. dist.,

marked  $\frac{1}{4}$  S 13 B T.

Continue descent of N. slope 26 ft. to

30.25 Small stream, 1 lk. wide, course NE.; ascend gradually along E. slope 20 ft. to

32.75 Top of small spur, slopes NE; descend N. slope 100 ft. to

38.10 Stream, 15 lks. wide, course SW; ascend S. slope 15 ft. to

39.57 Intersect the point for old cor. of Secs. 7, 12, 13 and 18, located by reference to the old bearing trees. I obliterate marks on the old SW and NW bearing trees