

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

N.0°05'E., resurveying the E. bdy. of Sec. 12.

Descend NW slope, through heavy timber and dense undergrowth, 240 ft. to

6.30 Ravine, course SW., ascend S. slope 115 ft. to

8.68 Intersect the old $\frac{1}{4}$ Sec. cor., which is a stone, firmly set, marked and witnessed as described by the Surveyor General. The old SE bearing tree is dead. I obliterate marks on the old SW bearing tree and change this cor. to refer to Sec. 7 only and alongside the old cor. set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 7 only, with brass cap marked

$\frac{1}{4}$
| S7
1919

from which

A Fir, 9 ins. diam., bears N.86°E., 13 lks. dist., marked $\frac{1}{4}$ S 7 B T.

A Fir, 12 ins. diam., bears S.75°E., 21 lks. dist., marked $\frac{1}{4}$ S 7 B T.

From this cor.

N.1°02'W., resurveying the E. bdy. of Sec. 12.

Ascend along W and SW slope 170 ft. to

7.50 Top of spur, slopes W; descend steep NW slope 600 ft. to

21.85 Ravine, course NE; ascend gradually along E. slope.

23.75 Top of low spur, slopes NE; descend N. slope 85 ft. to

25.64 Wasson Creek, 15 lks. wide, course W; ascend SE slope 120 ft. to

31.32 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 12 only, with brass cap marked

$\frac{1}{4}$
S12 |
1919

from which