

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

A Hemlock, 36 ins. diam., bears S.78\*W., 33 lks.  
dist., marked  $\frac{1}{2}$  S 12 B T.

An Alder, 12 ins. diam., bears N.62\*W., 36 lks.  
dist., marked  $\frac{1}{2}$  S 12 B T.

Continue ascent of SE slope 190 ft. to

38.69 Intersect the point for old cor. of Secs. 1, 6, 7 and  
12, located by reference to the old NW bearing tree.  
At the exact cor. point set an iron post, 3 ft. long,  
1 in. diam., 26 ins. in the ground, for angle point,  
with brass cap marked

AP  
1919

from which

A Fir, 12 ins. diam., bears N.20\*E., 34 lks.  
dist., marked A P B T (New B.T.)

A Fir, 14 ins. diam., bears N.63\*W., 24 lks.  
dist., marked A P B T (Old B.T.)

From this point

N.0\*41'W., resurveying the E. bdy. of Sec. 12.

Ascend SE slope 30 ft. to

0.90 Top of spur, slopes SW; descend NW slope 90 ft. to

14.05 Ravine, course SW; ascend 65 ft. to

15.95 Top of spur, slopes SW; descend 17 ft. to

19.50 Ravine, course NW; ascend 20 ft. to

20.71 Intersect the point for old closing cor. of Secs. 6 and  
7, located by reference to the old bearing trees,  
which are as described by the Surveyor General. At  
the exact cor. point set an iron post, 3 ft. long,  
2 ins. diam., 24 ins. in the ground, for closing cor.  
of Secs. 6 and 7, with brass cap marked

T21S  
S6 CC  
S7  
R9W  
1919