

RESURVEY EAST BOUNDARY T. 21 S., R. 10 W.

CHAINS

From this corner.

N.0°27'W., resurveying the E. bdy. of Sec. 12.

Ascend SE slope 270 ft. to

11.20 Top of ridge, bears NE and SW; descend NW slope 30 ft.
to

11.93 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of Secs. 1 and 12, with brass
cap marked

T21S
S1
S12
R10W
1919

from which

A Fir, 22 ins. diam., bears S.33°W., 65 lks. dist.,
marked T 21 S R 10 W S 12 B T.

A Fir, 36 ins. diam., bears N.10°W., 43 lks. dist.,
marked T 21 S R 10 W S 1 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold on sand-
stone base; 2nd rate.

Timber, Fir, Cedar, Hemlock and Maple.

Undergrowth, Salmonberry, Vinemaple and Salal.

N.0°27'W., resurveying the E. bdy. of Sec. 1.

Descend NW slope, through heavy timber and scattering
undergrowth, 250 ft. to

7.33 Intersect the point for the old $\frac{1}{2}$ Sec. cor., located by
reference to the old bearing trees, which are marked
as described by the Surveyor General. I now destroy
all evidence of this cor. and continue my line.

Descend N. slope 400 ft. to

17.00 Dry bed of creek in canyon, course NW; ascend SW slope
250 ft. to

28.45 Top of spur, slopes W; descend NW slope 180 ft. to

33.70 Ravine, course NW; ascend SW slope 210 ft. to