

## RESURVEY SOUTH BOUNDARY T. 21 S. R. 10 W.

CHAINS

- Continue ascent of SE slope 70 ft. to
- 10.55 Top of spur, slopes S; descend SW slope 140 ft. to
- 16.40 Stream, 1 lk. wide, course S; ascend SE slope 260 ft. to
- 26.55 Top of ridge, bears NE and SW; trail along top; descend  
NW slope 240 ft. to
- 38.51 Intersect the point for old cor. of Secs. 1 and 2,  
located by reference to the old bearing trees. At the  
exact cor. point set an iron post, 3 ft. long, 2 ins.  
diam., 24 ins. in the ground, for cor. of Secs. 1 and  
2, with brass cap marked

S2	S1
T22S	R10W
1919	

from which

A Fir, 12 ins. diam., bears S.55\*E., 24 lks. dist.  
marked T 22 S R 10 W S 1 B T. (Old B.T.)

A Cedar, 30 ins. diam., bears S.68\*W., 30 lks. dist.,  
marked T 22 S R 10 W S 2 B T (Old B.T.)

From this corner

N.89\*37\*W., resurveying the S bdy. of Sec. 36.

Ascend NE slope 125 ft. to

- 6.77 (A point S. of the cor. of Secs. 23, 24, 25 and 26)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground, for cor. of Secs. 35 and 36, with brass  
cap marked

T21S	R10W
S35	S36

1919

from which

A Fir, 14 ins. diam., bears N.39\*E., 39 lks. dist.  
marked T 21 S R 10 W S 36 B T.

A Fir, 60 ins. diam., bears N.53\*W., 82 lks. dist.  
marked T 21 S R 10 W S 35 B T.

Land, mountainous.

Soil, sandy loam and vegetable mold on sandstone base,