

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

brass cap marked

1/4 S35
1919

from which

A Fir, 6 ins. diam., bears N.21*E., 16 lks. dist.,
marked 1/4 S 35 B T.

A Fir, 16 ins. diam., bears N.79*W., 6 lks. dist.,
marked 1/4 S 35 B T.

- 7.65 Top of small spur, slopes SW; descend W. slope 200 ft. to
- 12.05 Ravine, course SE; ascend SE slope 290 ft. to
- 19.35 Top of spur, slopes SW; descend steep W slope 220 ft. to
- 23.35 Ravine, course SW; ascend steep SE slope 200 ft. to
- 33.25 Top of spur, slopes SW; descend steep W. slope 220 ft. to
- 40.70 Intersect the old cor. of Secs. 2 and 3, which is an

Alder tree, marked and witnessed as described by the
Surveyor General. Alongside the old cor. set an iron
post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,
for cor. of Secs. 2 and 3, with brass cap marked

S3 | S2
T22S R10W
1919

from which

An Alder, 7 ins. diam., bears S.70*E., 15 lks.
dist., marked T 22 S R 10 W S 2 B T.

An Alder, 10 ins. diam., bears S.5*W., 20 lks.
dist., marked T 22 S R 10 W S 3 B T.

From this corner

N.89*03'W., resurveying the S bdy. of Sec. 35.

Descend NW slope 135 ft. to

- 6.49 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of Secs. 34 and 35, with brass
cap marked

T21S R10W
S34 | S35

1919

from which