

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

A Fir, 8 ins. diam., bears N.51*E., 24 lks. dist.,
marked T 21 S R 10 W S 35 B T.

A Fir, 10 ins. diam., bears N.18*W., 28 lks. dist.,
marked T 21 S R 10 W S 34 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold on sandstone
base; 2nd and 3rd rate.

Timber, Fir, Cedar and Hemlock.

Undergrowth, Alder, Salmonberry, Salal and Vinemaple.

N.89*03'W., resurveying the S bdy. of Sec. 34.

Descend along N slope, through small timber and dense
undergrowth, 40 ft. to

- 1.80 Top of spur, slopes SE; descend W slope 235 ft. to
6.75 Dry creek bed, course SE; ascend NE slope 55 ft. to
11.15 Top of spur, slopes SE; descend W slope 215 ft. to
18.60 Small stream, course S; descend along N and NW slope
175 ft. to corner.

- 33.29 Intersect the point for old $\frac{1}{4}$ Sec. corner, located by
reference to the old bearing trees. At the exact
cor. point set an iron post, 3 ft. long, 1 in. diam.,
26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 3
only, with brass cap marked

$\frac{1}{4}$ ——— S3
1919

from which

A Cedar, 48 ins. diam., bears S.62*E., 49 lks.
dist., marked $\frac{1}{4}$ S 3 B T.

A Maple, 12 ins. diam., bears S.39*W., 87 lks.
dist., marked $\frac{1}{4}$ S 3 B T.

From this corner

S.89*49'W., resurveying the S bdy. of Sec. 34.

Ascend SE slope 185 ft. to

- 6.71 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 34 only, with