

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

brass cap marked

$\frac{1}{2}$  S34

1919

from which

A Maple, 14 ins. diam., bears N.61\*E., 67 lks. dist.  
marked  $\frac{1}{2}$  S 34 B T.

A Cherry, 6 ins. diam., bears N.70\*W., 40 lks. dist.  
marked  $\frac{1}{2}$  S 34 B T.

Continue ascent 110 ft. to

- 9.30 Top of spur, slopes S; descend SW slope 375 ft. to
- 22.45 Ravine, course SW; ascend NE slope 415 ft. to
- 35.45 Intersect the old cor. of Secs. 3 and 4, which is a

stone, firmly set, marked and witnessed as described  
by the Surveyor General. Alongside old stone set an  
iron post, 3 ft. long, 2 ins. diam., 24 ins. in the  
ground, for cor. of Secs. 3 and 4, with brass cap  
marked

S4 | S3  
T22S R10W  
1919

from which

An Alder, 8 ins. diam., bears S.80\*E., 4 lks. dist.  
marked T 22 S R 10 W S 3 B T (Old B.T.)

An Alder, 9 ins. diam., bears S.38\*W., 14 lks. dist.,  
marked T 22 S R 10 W S 4 B T (Old B.T.)

From this corner

West, resurveying the S bdy. of Sec. 34.

Ascend NE slope 340 ft. to

- 8.90 Top of spur ridge, bears NW and SE; descend SW slope  
40 ft. to
- 11.58 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
the ground, for cor. of Secs. 33 and 34, with brass  
cap marked

T21S R10W  
S33 | S34

1919