

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

brass cap marked

$\frac{1}{4}$ S33
1919

from which

A Fir, 5 ins. diam., bears N.23*E., 28 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.

A Fir, 8 ins. diam., bears N.76*W., 23 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.

Descend SW and S slope 310 ft. to creek.

43.85 Ravine, course SW; descend along S slope.

46.15 Descend SW slope.

49.05 Franklin Creek, 6 lks. wide, course SE; ascend NE slope
240 ft. to

53.85 Top of spur, slopes N; descend 25 ft. to

56.85 Stream, 3 lks. wide, course NE; ascend SE slope 345 ft.
to

64.55 Top of spur, slopes NE; descend along N and NW slope
25 ft. to

67.87 Intersect the point for old cor. of Secs. 4 and 5,
located by reference to the old bearing trees, which
are dead but marked as described by the Surveyor
General. At the exact cor. point set an iron post,
3 ft. long, 2 ins. diam., 24 ins. in the ground, for
cor. of Secs. 4 and 5, with brass cap marked

$\frac{S5}{T22S}$ $\frac{S4}{R10W}$
1919

from which

A Fir, 14 ins. diam., bears S.75*E., 40 lks. dist.,
marked T 22 S R 10 W S 4 B T.

An Alder, 12 ins. diam., bears S.31*W., 60 lks. dist.,
marked T 22 S R 10 W S 5 B T.

From this corner

N.89*46'W., resurveying the S bdy. of Sec. 33.

Ascend NE slope 75 ft. to