

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

2.35 Top of spur, slopes N; descend NW slope 40 ft. to
 3.55 Ravine, course N; ascend along N. slope 65 ft. to
 6.65 Ravine, course NE; ascend E slope 160 ft. to
 10.05 Summit of ridge, bears N and S; descend 60 ft. to
 12.13 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of Secs. 32 and 33, with brass
 cap marked

T21S R10W
S32|S33

1919

from which

A Willow, 12 ins. diam., bears N.60*E., 46 lks. dist.
 marked T 21 S R 10 W S 33 B T.

A Fir, 16 ins. diam., bears N.65*W., 57 lks. dist.,
 marked T 21 S R 10 W S 32 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold; 2nd and 3rd
 rate.

Timber, Alder, Maple and Fir.

Undergrowth, Salmonberry, Huckleberry, Salal and
 Vinemaple.

N.89*46*W., resurveying the S bdy. of Sec. 32.

Descend along N. slope, through scattering timber and
 dense undergrowth, 100 ft. to

3.45 Ascend NE slope 30 ft. to
 7.35 Top of spur, slopes N; descend along N. slope 35 ft. to
 10.45 Draw, course N; ascend NE slope 75 ft. to
 13.05 Top of ridge, bears N and S; descend NW slope 140 ft. to
 17.25 Ravine, course N; ascend along N slope 80 ft. to
 23.05 Top of ridge, bears NW and SE; descend W slope 185 ft. to
 27.46 Apportioned distance
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
 ground, for $\frac{1}{2}$ Sec. cor. of Sec. 5 only, with brass
 cap marked