

RESURVEY SOUTH BOUNDARY T. 21 S., R. 10 W.

CHAINS

Surveyor General. Alongside the old cor. set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 5 and 6, with brass cap marked

S6	S5
T22S	R10W
1919	

from which

A Fir, 8 ins. diam., bears S.49°E., 21 lks. dist., marked T 22 S R 10 W S 5 B T (New B.T.)

A Fir, 42 ins. diam., bears S.82°W., 50 lks. dist., marked T 22 S R 10 W S 6 B T (Old B.T.)

From this corner

N.89°38'W., resurveying the S bdy. of Sec. 32.

Ascend NE slope 20 ft. to

0.55 Top of spur, slopes N; descend NW slope 25 ft. to

1.57 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 31 and 32, with brass cap marked

T21S	R10W
S31	S32

1919

from which

An Alder, 12 ins. diam., bears N.20°E., 11 lks. dist., marked T 21 S R 10 W S 32 B T.

A Fir, 10 ins. diam., bears N.20°W., 8 lks. dist., marked T 21 S R 10 W S 31 B T.

Land, mountainous.

Soil, shallow sandy loam on sandstone base; 2nd and 3rd rate.

Timber, Fir, Alder and Maple.

Undergrowth, Salmonberry, Vinemaple and Salal.

N.89°38'W., resurveying the S bdy. of Sec. 31.

Descend NW slope, through heavy timber and dense undergrowth, 140 ft. to