

RESURVEY PORTION WEST BOUNDARY T. 21 S., R. 10 W.

CHAINS

73.90 Top of spur, slopes NE; descend 120 ft. to

76.00 Apportioned distance

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 24 and 25, with brass cap marked

T21S	
S24	
S25	
R11W	
1919	

from which

A Fir, 12 ins. diam., bears S.63*W., 15 lks. dist., marked T 21 S R 11 W S 25 B T.

A Fir, 10 ins. diam., bears N.87*W., 17 lks. dist., marked T 21 S R 11 W S 24 B T.

Continue descent of N. slope 115 ft. to

78.80 Creek, 6 lks. wide, course E; ascend S slope 20 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 19 and 30, with brass cap marked

T21S	
S19	
S30	
R10W	
1919	

from which

A Fir, 14 ins. diam., bears N.63*E., 24 lks. dist., marked T 21 S R 10 W S 19 B T.

A Fir, 14 ins. diam., bears S.17*E., 24 lks. dist., marked T 21 S R 10 W S 30 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold; 2nd and 3rd rate.

Timber, Fir, Hemlock, Cedar, Maple and Alder.

Undergrowth, Salmonberry, Vinemaple and Salal.

N.0*06'W., resurveying the W bdy. of Sec. 19.

Ascend S slope, through heavy timber and dense undergrowth, 290 ft. to